

# AHRI 1060-2005

## Certified Performance

AHRI-1060 Certified Performance - Model Number L85-G5													
Type		Tilt Angle			Nominal Airflow				Pressure Drop				
Plate		N/A			100% - 450 SCFM 75% - 338 SCFM				0.6 in. H <sub>2</sub> O 0.5 in. H <sub>2</sub> O				
Leakage Ratings					Thermal Effectiveness Ratings at 0" Pressure Differential								
	Pressure Differential	EATR	OACF	Purge Angle or Setting	Nominal Airflow	Sensible	Latent	Total	Net Airflow	Net Sensible	Net Latent	Net Total	
Test 1	-1 in. H <sub>2</sub> O	1.0%	1.00	N/A	450 Heating CFM Cooling	73%	53%	66%	450 CFM	73%	53%	66%	
Test 2	0 in. H <sub>2</sub> O	0.0%	1.02	N/A	338 Heating CFM Cooling	73%	46%	56%	338 CFM	73%	46%	56%	
Test 3	1 in. H <sub>2</sub> O	0.0%	1.05	N/A		77%	60%	71%		77%	60%	71%	

AHRI-1060 Certified Performance - Model Number L125-G5													
Type		Tilt Angle			Nominal Airflow				Pressure Drop				
Plate		N/A			100% - 750 SCFM 75% - 563 SCFM				0.65 in. H <sub>2</sub> O 0.45 in. H <sub>2</sub> O				
Leakage Ratings					Thermal Effectiveness Ratings at 0" Pressure Differential								
	Pressure Differential	EATR	OACF	Purge Angle or Setting	Nominal Airflow	Sensible	Latent	Total	Net Airflow	Net Sensible	Net Latent	Net Total	
Test 1	-1 in. H <sub>2</sub> O	1.0%	1.00	N/A	750 Heating CFM Cooling	71%	52%	64%	750 CFM	71%	52%	64%	
Test 2	0 in. H <sub>2</sub> O	0.0%	1.02	N/A	563 Heating CFM Cooling	71%	43%	53%	563 CFM	71%	43%	53%	
Test 3	1 in. H <sub>2</sub> O	0.0%	1.05	N/A		75%	59%	69%		75%	59%	69%	

NOTE: SCFM = Standard Cubic Feet per Minute OACF = Outdoor Air Correction Factor EATR = Exhaust Air Transfer Ratio N/A = Not Applicable

Energy recovery component certified in accordance with AHRI Standard 1060-2005.  
Actual performance in packaged equipment may vary.



## MODEL NUMBERING GUIDE CA & PA MODELS

